| | 3-pins EE13/6/6 o | coll former | | | | |
|---|---|--|---|------------------------|---|---|
| PARA | METER | SPECIFICATION | | | | |
| Coil former mate | erial | phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481 | | | | |
| Pin material | | copper-tin alloy (CuSn), tin (Sn) plated | | | | |
| Maximum opera | ating temperature | 180°C, "IEC 60085", class H | | | | |
| Resistance to se | oldering heat | "IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s | | | | |
| Soldeerability | | "IEC 60068-2-20", Part 2, Test Ta, method 1 | | | | |
| | | | | | | |
| SC | | | | | | |
| 11.40 | | | | | | |
| Winding data a | and area product | for 8-pins EE | 13/6/6 coi | l forme | r | |
| | WINDING | MINIMUM WINDING | AVERAGE LENGTH OF TURN (mm) | | AREA PRODUCT Ae x Aw | TYPE NUMBER |
| NUMBER OF SECTIONS | AREA (mm ²) | WIDTH (mm) | | | (mm ⁴) | |
| | | | (m | | | EE-1309-1S-8P |
| SECTIONS 1 | (mm ²) | (mm) 7.60 Dim | ensions: | m) | (mm ⁴) 225 | EE-1309-1S-8P |
| SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<l≤<="" td=""><td>(mm²) 14 otherwise specified: ≤16±0.20</td><td>(mm) 7.60 Dim</td><td>ensions:</td><td>m)</td><td>(mm⁴) 225 RE</td><td></td></l≤4±0.10> | (mm ²) 14 otherwise specified: ≤16±0.20 | (mm) 7.60 Dim | ensions: | m) | (mm ⁴) 225 RE | |
| SECTIONS 1 Tolerances unless of 0 <ls4±0.10< td=""> 4<l5< td=""> 16<l≤45±0.30< td=""> 45</l≤45±0.30<></l5<></ls4±0.10<> | (mm ²) 14 | (mm) 7.60 | ensions: | Mould No. | (mm ⁴) 225 RE | MARK |
| SECTIONS 1 Tolerances unless of 0 <ls4±0.10< td=""> 4<l5< td=""> 16<l≤45±0.30< td=""> 45</l≤45±0.30<></l5<></ls4±0.10<> | (mm ²) 14 otherwise specified: <16±0.20 5 <l±0.40< td=""><td>(mm) 7.60</td><td>ensions:</td><td>Mould No.</td><td>(mm⁴) 225 RE</td><td>MARK Bobbin material: T378J</td></l±0.40<> | (mm) 7.60 | ensions: | Mould No. | (mm ⁴) 225 RE | MARK Bobbin material: T378J |
| SECTIONS 1 Tolerances unless of 0 <l≤4±0.10< td=""> 16<l≤45±0.30< td=""> 45 Pin Dim:±0.05 Thick</l≤45±0.30<></l≤4±0.10<> | (mm ²) 14 otherwise specified: <16±0.20 5 <l±0.40< td=""><td>(mm) 7.60 Dim () h:±0.20</td><td>(m 3 ensions: mm) C ctronics 14-8769358</td><td>Mould No. Code No.:</td><td>(mm⁴) 225 RE FAY01146</td><td>MARK Bobbin material: T378J Available for Fuan core: EE13/6/6</td></l±0.40<> | (mm) 7.60 Dim () h:±0.20 | (m 3 ensions: mm) C ctronics 14-8769358 | Mould No. Code No.: | (mm ⁴) 225 RE FAY01146 | MARK Bobbin material: T378J Available for Fuan core: EE13/6/6 |

COIL FORMER General data 8-pins EE13/6/6 coil former