General data 1	4-pins ER42/22	/15 coil former			
PARAMETER		SPECIFICATION			
Coil former mat	erial	phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481			
Pin material		copper-tin alloy (CuSn), tin (Sn) plated			
Maximum operating temperature		180°C, "IEC 60085", class H			
Resistance to soldering heat		"IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s			
Soldeerability		"IEC 60068-2-20", Part 2, Test Ta, method 1			
	-Ø18.2 -Ø16.10			4.00	
Winding data a	- 16.70	2.00 40.00	242/22/15 coil fo		
			1		
NUMBER OF SECTIONS	WINDING AREA (mm ²)	MINIMUM WINDING WIDTH (mm)	AVERAGE LENGTH OF TURN (mm)	AREA PRODUCT Ae x Aw (mm ⁴)	TYPE NUMBER
1	144	27.20	74	24480	ER-4203-1-1S-14P
0 <l≤4±0.10 4<l<br="">16<l≤45±0.30 45<="" td=""><td>otherwise specified: ≤16±0.20 5≤L±0.40</td><td>(m</td><td></td><td>: ER4203-1</td><td>MARK Bobbin material: T378J</td></l≤45±0.30></l≤4±0.10>	otherwise specified: ≤16±0.20 5≤L±0.40	(m		: ER4203-1	MARK Bobbin material: T378J
	ckness:±0.20 Pin Pito	+		FAY01091	Available for Fuan core: ER42/22/15
		Fuan Electronics		Make: P.Xiao	Material Number: A47420310100
			EML :sales@fuantronics.net WEB:www.fuantronics.net		
	AIRUI	EML :sales@fu	antronics.net	Checked: Beson. zhan Approved: Anson. zhan	Document/Rev: 00 Date of Recognition: Oct./09/2019

COIL FORMER General data 14-pins ER42/22/15 coil former