


## **COIL FORMER**


## General data 12-pins PQ20/20 coil former

PARAMETER	SPECIFICATION
Coil former material	phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481
Pin material	copper-tin alloy (CuSn), tin (Sn) plated
Maximum operating temperature	180°C, "IEC 60085", class H
Resistance to soldering heat	"IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s
Soldeerability	"IEC 60068-2-20", Part 2, Test Ta, method 1









## Winding data and area product for 12-pins PQ20/20 coil former

NUMBER OF SECTIONS	WINDING AREA (mm²)	MINIMUM WINDING WIDTH (mm)	AVERAGE LENGTH OF TURN (mm)	AREA PRODUCT Ae x Aw (mm <sup>4</sup> )	TYPE NUMBER
1	37	12.00	45	2220	PQ-2020-1-1S-12P

Tolerances unless otherwise specified:  $0 < L \le 4 \pm 0.10$   $4 < L \le 16 \pm 0.20$   $16 < L \le 45 \pm 0.30$   $45 \le L \pm 0.40$  Pin Dim: $\pm 0.05$  Thickness: $\pm 0.20$  Pin Pitch: $\pm 0.20$ 

D	Dimensions: (mm)	REMARK		
		Mould No.	: PQ2020-1	Bobbin material: T378J
		Code No.: FAY01091		Available for Fuan core: PQ20/20
_				



## **Fuan Electronics**

TEL :0086-514-87693589 EML :sales@fuantronics.net WEB:www.fuantronics.net

Make: P.Xiao	Material Number: A42200300100	
Checked: Beson. zhan	Document/Rev: 00	
Approved: Anson. zhan	Date of Recognition: Oct./09/2019	